
ADHESION PROMOTION FOR POWDER COATINGS TEGO[®] Powder Aid C01

Polyester-modified polymer for anti-corrosion & adhesion promotion




Powder coatings are available in a wide range of finishes and colors and are renowned for their exceptional durability. This makes them well-suited for architectural applications such as outdoor stadium seating, window and door frames, as well as various types of furniture. These demanding uses drive the need for enhanced corrosion resistance.

Extensive laboratory testing across multiple binder technologies has demonstrated that TEGO[®] Powder Aid C01 significantly boosts corrosion protection in single-layer powder coating systems.

This additive, based on modified polyester polymers, introduces a novel approach to performance enhancement in powder coatings. This innovative technology provides a smoother surface finish and improved film flexibility compared to the incumbent technologies.

TEGO[®] Powder Aid CO1 is supplied as free-flowing granules that are easily incorporated into the premix prior to extrusion. No special handling is required, making it a user-friendly and efficient solution for improving coating performance.




.....



Click or scan the QR-code for more information!


TEGO® Powder Aid C01 optimizes corrosion protection and adhesion properties of the coating

Test formulation Blank sample +3% TEGO[®] Powder Aid C01 +5 % TEGO[®] Powder Aid C01



860 hours salt spray test Cold rolled steel panels Single layer, DFT ~ 80-85 μm | Curing conditions: 15' 180°C

The gloss retention when using TEGO[®] Powder Aid C01 is significantly higher than with a silica-based benchmark




This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its uitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OF IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NONINFRINGEMENT, MERCHANTABILITY AND / OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and /or recommendations at any time, without prior or subsequent notice. ACEMATT*, ADDID*, AEROSIL*, AIRAS*, ALBIDUR*, CARBOWET*, DYNOL*, NANOCRYL*, SILIKOPTAL*, SILIKOPHEN*, SILIKOPON*, SILIKOPDR*, SILIKOTOP*, SIPERNAT*, SURFYNOL*, TEGO*, TEGOMER* and ZETASPERSE* are registered trademarks of Evonik Industries or its subsidiaries. Evonik supports you in selecting the best suited product and optimizing current formulations through our Application Technology Group.

TEST FORMULATION – BLANK SAMPLE

Polyester resin	61.8
ß-HAA crosslinker	3.2
Degassing agent	0.3
Flow/levelling agent	1.0
Pigment TiO ₂	22.5
Filler	11.2
Total	100.0

+3% TEGO° Powder Aid C01



+3% benchmark silica based product



EVONIK OPERATIONS GMBH Goldschmidtstraße 100 45127 Essen Germany Phone +49 201 173-2222 coating-additives@evonik.com www.coating-additives.com

