

# ISO-BUTANE

## CAS NO.

75-28-5

## APPLICATIONS & PROPERTIES

iso-Butane is a colorless, inflammable gas with a characteristic odor. Under pressure, this gas is easily condensable.

## TRANSPORT & LOGISTICS

The delivery takes place in tank cars, rail tank cars, containers and tankers.

## APPLICATION FIELDS

Iso-Butane is useful as a solvent for manufacturing of polyethylenes as well as propellants (e.g., for construction foam) and alkylate petrol.

## SPECIFICATION

Property	Value	Unit	Method
iso-Butane	min. 95	% (m/m)	GC: QS-AA 04-010 *
n-Butane	max. 5	% (m/m)	GC: QS-AA 04-010 *
Propane	max. 1	% (m/m)	GC: QS-AA 04-010 *
Olefine	max. 200	mg/kg	GC: QS-AA 04-010 *
1,3-Butadiene	max. 1	mg/kg	GC: QS-AA 04-011 *

\* in-house method

**Disclaimer**

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

**Evonik Oxeno GmbH & Co. KG**

Paul-Baumann-Straße 1

45772 Marl

C4-chemicals@evonik.com

[www.evonik.com/c4-chemicals](http://www.evonik.com/c4-chemicals)