

DYNACOLL® Terra 7750

preliminary

03.21

General discription

Solid, crystalline and saturated polyester polyol made of 100 % b.w. renewable materials.

Application

Manufacturing of biobased reactive hot melt adhesives with moderately setting behaviour.

Specification

Property	Value	Unit	Test method
Hydroxyl number	27 – 34	mg KOH/g	DIN EN ISO 4629-2
Acid number	max. 2	mg KOH/g	DIN EN ISO 2114

Typical data

Molecular weight	3500	-	calculated from Hydroxyl number
Melting point	55	°C	DSC
Softening point (R + B)	65	°C	DIN ISO 4625
Viscosity at 80 °C	2	Pa s	DIN EN ISO 3219

Compatibility with other DYNACOLL copolyesters (1:1 blends)

Transparent: 7110, 7130, 7131, 7150, 7230, 7231, 7250, 7255, 7320, 7340, 7360, 7361, 7365, 7380

Terra 7540, 7640, EP 413.04, EP 424.02

Cloudy: 7330, 7363, 7381, 7390

Opaque: 7111

Terra EP 413.02

Phase Separation: 7140, 7210

Terra 7530

Form supplied

190 kg drums.

Storage Stability

When stored below 30 °C in closed containers the product remains stable for at least one year from delivery. In case of open or improperly closed containers, there is a possibility of increased moisture from the atmosphere.

Safety and Handling

Please refer to our Material Safety Data Sheet.

Reactive Hot Melt Typical data

Reaction product from DYNACOLL Terra 7750 with 4,4-MDI (Diphenylmethane-4,4'-diisocyanate) in a ratio OH/NCO = 1/2.2

Property	Value	Unit	Test method
Softening point (R + B)	65	°C	DIN ISO 4625
Open time	15	min	Evonik internal method
Setting time	5	min	Evonik internal method
Viscosity at 130 °C	4	Pa s	Parallel plate
Tensile strength	20	N/mm ²	DIN 53 504
Elongation at break	450	%	DIN 53 504

Evonik Operations GmbH

Paul-Baumann-Str. 1 45764 Marl Germany PHONE +49 2365 49-02

FAX +49 2365 49-5030

Evonik Corporation

Resource Efficiency 299 Jefferson Road Parsippany, NJ 07054-0677, USA Xinzhuang Industry Park PHONE +1 973 929-8000

Fax +1 973 929-8460 **Evonik Specialty Chemicals** (Shanghai) Co., Ltd.

55, Chundong Road Shanghai, 201108, PR China PHONE +86 21 6119-1028 FAX +86 21 6119-1254

Email adhesives@evonik.com www.evonik.com/adhesives-sealants www.evonik.com/designed-polymers

Marl, March 24, 2021

DYNACOLL® is a registered trademark of Evonik Industries AG or one of its subsidiaries

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.