

Product Information VISIOMER® MPEG 5005 MA W

Methoxypolyethylene glycol 5000-methacrylate 50 % in water

CAS-No.: 26915-72-0

Quality on supply

Appearance: at room temperature clear, colorless to yellowish liquid

Odor: faintly ester-like

Standard specification

		Test Method	
Acid number	max. 20 mg KOH/g	M4	(acid-base-titr., calculated
	(= max. 3.1 % GMAA)		as GMAA)
Water content	50 ± 2 %	М3	(according to K. Fischer)
Stabilization	200 ± 20 ppm MEHQ	M1-1	(HPLC)
Degree of conversion	> 95 mol%	M94	(NMR)



Following data are not part of the product specification but serve as benchmarks.

Physical Data

Molecular weight	~ 5000 g/mol	
Density	~ 1.08 g/cm³ at 20 °C	
Refractive index	approx. 1.408 at 20 °C	
Boiling point	100 °C (water) (1013 hPa)	
Vapor pressure	approx. 23 hPa (20 °C)	
Melting temperature	< 4 °C	
Viscosity	~ 180 mPa·s at 15 °C	
	~ 145 mPa·s at 20 °C	
	~ 125 mPa·s at 23 °C	
	~ 115 mPa·s at 25 °C	
	~ 90 mPa·s at 30 °C	
Solubility	miscible	
Molecular weight	~ 5000 g/mol	

Registration

REACH	pre-registered, registered or exempted
included in TSCA	+

General Hints

For information about health protection and shipment see our Safety Data Sheet

Application

Waterbased coatings, polymerisable emulsifier, textile and water treatment, paper production, additive for concrete.

Shelf life of the standard stabilized product: 6 months at max. 30 °C from date of delivery

Ref.-No.: VISIOMER® MPEG 5005 MA W / FM 517-e - 08/2013

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

* = registered trademark

Evonik Operations GmbH Specialty Methacrylates Kirschenallee 64293 Darmstadt Germany

visiomer@evonik.com www.visiomer.com www.evonik.com

