AEROSIL® 🆃

Product information

AEROSIL[®] NX 90 S

Hydrophobic fumed silica

the second second second second second

| Characteristic physico-chemical data | | |
|--|------|------------|
| Properties and test methods | Unit | Value |
| Specific surface area (BET) | m²/g | 50 - 80 |
| pH value** in 4% dispersion | | 5.0 - 7.5 |
| Loss on drying** 2 hours at 105 °C | % | ≤ 0.5 |
| C content | % | 0.5 - 1.5 |
| Bulk density | g/I | approx. 40 |
| SiO ₂ content based on ignited material | % | ≥ 99.8 |
| Triboelectric charge* | μC/g | - 300 |
| * Evonik method ** ex plant The data represents typical values (no product specification). | | |

Registrations (substance or product components)

AEROSIL® NX 90 S

| CAS-No. | 68909-20-6 |
|---------------------|------------|
| REACH (Europe) | exempted |
| TSCA (USA) | registered |
| DSL (Canada) | registered |
| AICS (Australia) | registered |
| ENCS (Japan) | registered |
| IECSC (China) | registered |
| KECI (Korea) | registered |
| PICCS (Philippines) | registered |
| | |

AEROSIL® NX 90 S is a hydrophobic fumed silica treated with HMDS. Which has an improved dispersibility compared with AEROSIL® NX 90 G and a negative electrostatic charge and provides efficient free flow aid for toners and dry powders in general. This product is applied to reduce the moisture pick-up behaviour of dry powders. This product is also enhancing durability of toners.

Applications and properties

Applications

• Toner

Properties

- has a negative tribo-charge and provides a high charge stability to toners
- is applied to reduce the moisture pick-up
- can compatible both flowability of toner and enhancement of durability as a spacer

Safety and handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Evonik Operations, Product Safety Department, E-MAIL sds-im@evonik.com We recommend to read carefully the safety data sheet prior to the use of our product.

Packaging and storage

AEROSIL® NX 90 S is supplied in multiple layer 5 kg bags. We recommend to store the product in closed containers under dry conditions and to protect the material from volatile substances. AEROSIL® NX 90 S should be used within two years after production.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Customer Service

Europe/ Middle-East/ Africa/ Latin America Evonik Operations GmbH

Business Line Silica PB 010-A410 Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany PHONE +49 6181 59 12532 FAX +49 6181 59 712532 aerosil@evonik.com www.silica-specialist.com

Technical Service

Europe/ Middle-East/ Africa/ Latin America

Evonik Operations Business Line Silica HPC 911-221 A Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany PHONE +49 6181 59-3936 FAX +49 6181 59 4489 technical.service.aerosil@ evonik.com www.silica-specialist.com

North America

Evonik Corporation Business Line Silica 299 Jefferson Road Parsippany, NJ 07054-0677 USA PHONE +1 800-233-8052 FAX +1 973-929-8502 aerosil@evonik.com www.silica-specialist.com

North America

Evonik Corporation Business Line Silica 2 Turner Place Piscataway, NJ 08855-0365 USA PHONE +1 888 SILICAS PHONE +1 732 981-5000 FAX +1 732 981-5275 technical.service.aerosil@ evonik.com www.silica-specialist.com

Asia (excluding Japan) Evonik (SEA) Pte. Ltd.

Business Line Silica 3 International Business Park Nordic European Centre, #07-18 Singapore 609927 PHONE +65 6809-6877 FAX +65 6809-6677 aerosil@evonik.com www.silica-specialist.com

Asia (excluding Japan)

Chemicals (Shanghai) Co.,Ltd

Evonik Specialty

Business Line Silica

55 Chundong Road

Shanghai 201108

P.R. China

evonik.com

Xinzhuang Industry Park

PHONE +86 21 6119-1151

FAX +86 21 6119-1075

technical.service.aerosil@

www.silica-specialist.com

Japan

NIPPON AEROSIL CO., LTD.

Marketing & Sales Division P.O. Box 7015 Shinjuku Monolith 13F 3-1, Nishi-Shinjuku 2-chrome Shinjuku-ku, Tokyo 163-0913 Japan PHONE +81 3 3342-1789 FAX +81 3 3342-1761 infonac@evonik.com www.aerosil.jp

Japan NIPPON AEROSIL CO., LTD.

Applied Technology Group 3 Mita-Cho Yokkaichi, Mie 510-0841 Japan PHONE +81 59 345-5270 FAX +81 59 346-4657 infonac@evonik.com www.aerosil.jp

