

Product information

Dynasylan® MTMS

Methyltrimethoxysilane

Technical data

Properties and test methods	Value	Unit	Method
Density (20 °C)	арргох. 0.96	g/cm³	DIN 51757
Viscosity (20 °C)	арргох. 0.5	mPa [·] s	DIN 53015
Flash point	арргох. 9	°C	DIN 51755
Initial boiling point	арргох. 102	°C	DIN 51751

Registrations

Dynasylan® MTMS

EINECS/ELINCS (EU):	Yes	
AICS (Australia):	Yes	
DSL/NDSL (Canada):	Yes	
PICCS (Philippines):	Yes	
TSCA (USA):	Yes	
IECS (P.R. China):	Yes	
ENCS (Japan):	Yes	
ECL (South Korea):	Yes	
REACH (Europe)	Registered	

Dynasylan® MTMS, an alkyltrialkoxysilane is an important component in **sol-gel systems**.

Dynasylan® MTMS is a colorless, low-viscosity liquid. Dynasylan® MTMS is regarded as trifunctional since all three alkoxy groups are able to hydrolyze. Additionally Dynasylan® MTMS contains a methyl group that adds organic character to the products. Hydrolysis leads to silanol groups which, in a subsequent condensation reaction, form very stable siloxane bonds (-Si-O-Si-). Condensation occurs parallel to hydrolysis once a certain amount of silanol groups have been formed. The absolute and relative rates of hydrolysis and condensation depend on a number of factors. The most important factors include pH, concentration, solvent, temperature and the catalyst.

Safety and handling

Before considering the use of Dynasylan® products please read its Safety Data Sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available after registration on our website www.dynasylan.com or upon request from your local representative, customer service or from Evonik Operations GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

Packaging, storage and shelf life

Dynasylan $^{\circ}$ MTMS are available in 25 kg, 190 kg and 900 kg drums/containers.

Dynasylan® MTMS must be stored with exclusion of moisture.

In originally sealed containers, Dynasylan® MTMS has a shelf life of min. 12 months from delivery.

Properties and applications

In some sol-gel applications Dynasylan® MTMS is partially hydrolyzed to form a preproduct that can be further crosslinked using temperature. This prehydrolysis often is done in conjunction with other organofunctional silanes (e.g. Dynasylan® GLYMO), silicic acid esters or even an aqueous silica sol. This preproduct can be modified even further by addition of organic resins or inorganic nanoparticles such as AEROSIL®.

It is also possible to construct an inorganic/organic network by adding silanes containing organofunctional groups (e.g. aminopropyl groups) and organic resins and polymerizing using standard organic methods. This principle makes it possible to obtain mar resistant coatings having a higher UV-stability than traditional organic coatings. This can also lead to more flame resistant materials than using traditional resins.

Reactivity

Dynasylan® MTMS reacts faster with water than Dynasylan® MTES

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND,WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Europe/Middle-East/Africa North America **Evonik Operations GmbH**

Silanes Business Line Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany FAX +49 6181 59 713915 dynasylan@evonik.com

Asia / Pacific Evonik (SEA) Pte. Ltd.

www.dynasylan.com

Silanes Business Line 3 Internatioanl Business Park #07-18, Nordic European Centre Singapore 609927 PHONE +65 6809 6906 FAX +65 6809 6699 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Japan Co. Ltd

Silanes Business Line 12th Floor Monolith Building 2-3-1, Nishi-Shinjuku-ku Tokyo 163-0912 Japan PHONE +81 353 23 7446 FAX +81 353 23 7397 dynasylan@evonik.com

www.dynasylan.com

Evonik Corporation Silanes Business Line

299 Jefferson Road Parsippany, NJ 07054 USA PHONE (TOLL FREE) +1 800 237 67 FAX +1 732 981 5275 45 PHONE +1 973 929 8513 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific **Evonik Specialty** Chemicals (Shanghai) Co. Ltd.

Silanes Business Line 55, Chungdong Road Xinzhuang Industry Park Shanghai 201108 P.R. China PHONE +86 21 61191-399 FAX +86 21 61191-648 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik India Pvt. Ltd.

Silanes Business Line Krislon House Saki Vihar Road, Anderi (E) Mumbai - 400 072 PHONE +91 226 7238 809 FAX +91 226 7238 811 dynasylan@evonik.com www.dynasylan.com

North America Silbond Corporation

9901 Sand Creek Highway Weston, MI 49289 USA PHONE +1 732 981 5004 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Korea Ltd. Silanes Business Line

3F (Nongshim Sungmookwan B/D) 112 Yeouidaebang-Ro Dongjak-Gu Seoul, 07057 Когеа PHONE +82 2320 4773 FAX +82 2783 2520 dynasylan@evonik.com www.dynasylan.com

Region Central and South America Evonik Brasil Ltda.

Silanes Business Line Rua Arquiteto Olavo Redig de Campos, Torre A - 04711-904 São Paulo- SP Brazil PHONE +55 11 3146 9627 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Taiwan Ltd.

Silanes Business Line Artist Construction Bldg. 9F, No. 133 Min Sheng East Road, Sec 3 Taipei, 105 Taiwan, R.O.C. Taiwan 10596 PHONE +886 227 17 1242 #247 FAX +886 227 17 2106 dynasylan@evonik.com www.dynasylan.com

