

Product information

Dynasylan® TRIAMO

Triamino-functional propyltrimethoxysilane

Technical data

Properties and test methods	Value	Unit	Method
Density (20 °C/ 68 °F)	арргох. 1.03	g/cm³	DIN 51757
Refractive index n (20,D)	арргох. 1.46	-	DIN 51423
Viscosity (20 °C/ 68 ° F)	арргох. 20	mPa·s / cSt	DIN 53015
Boiling point (2.7 hPa / 2 torr)	арргох. 114- 168	°C/ °F	DIN 51356
Flash point	approx. 137/ 302	°C/ °F	EN 22719

Registrations

Dynasylan® TRIAMO

EINECS/ELINCS (EU); REACH (Europe)	Yes; Registered
AICS (Australia):	Yes
DSL/NDSL (Canada):	Yes
PICCS (Philippines):	Yes
TSCA (USA):	Yes
IECS (P.R. China):	Yes
TCCL (South Korea):	Yes
Switzerland	Yes
ECS (Taiwan)	Yes
KKDIK (Turkey)	Yes

Dynasylan® TRIAMO is an organofunctional silane possessing three reactive amino groups and a hydrolyzable trimethoxysilyl group.

The dual nature of its reactivity allows Dynasylan® TRIAMO to bind chemically to both inorganic materials (e.g. glass, metals, fillers) and organic polymers (e.g. thermosets, thermoplastics, elastomers) thus functioning as an adhesion promoter and surface modifier. Dynasylan® TRIAMO is a clear, light to dark yellow liquid with a slight amine-like odor. It is soluble in alcohols, ketones, esters and aliphatic and aromatic hydrocarbon solvents.

Safety and handling

Before considering the use of Dynasylan® products please read its Safety Data Sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available after registration on our website www.dynasylan.com or upon request from your local representative, customer service or from Evonik Operations GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

Packaging, storage and shelf life

Dynasylan® TRIAMO is supplied in 25 and 200 kg drums.

In unopened container Dynasylan $\ensuremath{^{\circ}}$ TRIAMO has a shelf life of min. 12 months from delivery.

Properties and applications

Dynasylan® TRIAMO is used in applications such as:

- PVC-pastisols as an additive (ca. 0.5-1%) to improve adhesion between PVC and metals
- Foundry resins:

Important product effects that can be achieved through the use of Dynasylan® TRIAMO include:

- improved adhesion
- improved moisture and corrosion resistance

Reactivity

In the presence of water, the methoxy (Si-OCH₃) groups of Dynasylan® TRIAMO hydrolyze to form reactive silanol (Si-OH) groups which can bond to a variety of inorganic substrates.

The amine groups of Dynasylan $\ensuremath{^{\circ}}$ TRIAMO can react with a suitable polymer.

Dynasylan® TRIAMO may be used with PVC and silicones.

Processing

Dynasylan® TRIAMO may be added to polymer matrix as an additive.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND,WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Europe/Middle-East/Africa North America **Evonik Operations GmbH**

Silanes Business Line Rodenbacher Chaussee 4 63457 Hanau-Wolfgang Germany FAX +49 6181 59 713915 dynasylan@evonik.com

Asia / Pacific Evonik (SEA) Pte. Ltd.

www.dynasylan.com

Silanes Business Line 3 Internatioanl Business Park #07-18, Nordic European Centre Singapore 609927 PHONE +65 6809 6906 FAX +65 6809 6699 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Japan Co. Ltd

Silanes Business Line 12th Floor Monolith Building 2-3-1, Nishi-Shinjuku-ku Tokyo 163-0912 Japan PHONE +81 353 23 7446 FAX +81 353 23 7397 dynasylan@evonik.com

www.dynasylan.com

Evonik Corporation Silanes Business Line

299 Jefferson Road Parsippany, NJ 07054 USA PHONE (TOLL FREE) +1 800 237 67 FAX +1 732 981 5275 45 PHONE +1 973 929 8513 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific **Evonik Specialty** Chemicals (Shanghai) Co. Ltd.

Silanes Business Line 55, Chungdong Road Xinzhuang Industry Park Shanghai 201108 P.R. China PHONE +86 21 61191-399 FAX +86 21 61191-648 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik India Pvt. Ltd.

Silanes Business Line Krislon House Saki Vihar Road, Anderi (E) Mumbai - 400 072 PHONE +91 226 7238 809 FAX +91 226 7238 811 dynasylan@evonik.com www.dynasylan.com

North America Silbond Corporation

9901 Sand Creek Highway Weston, MI 49289 USA PHONE +1 732 981 5004 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Korea Ltd. Silanes Business Line

3F (Nongshim Sungmookwan B/D) 112 Yeouidaebang-Ro Dongjak-Gu Seoul, 07057 Когеа PHONE +82 2320 4773 FAX +82 2783 2520 dynasylan@evonik.com www.dynasylan.com

Region Central and South America Evonik Brasil Ltda.

Silanes Business Line Rua Arquiteto Olavo Redig de Campos, Torre A - 04711-904 São Paulo- SP Brazil PHONE +55 11 3146 9627 dynasylan@evonik.com www.dynasylan.com

Asia / Pacific Evonik Taiwan Ltd.

Silanes Business Line Artist Construction Bldg. 9F, No. 133 Min Sheng East Road, Sec 3 Taipei, 105 Taiwan, R.O.C. Taiwan 10596 PHONE +886 227 17 1242 #247 FAX +886 227 17 2106 dynasylan@evonik.com www.dynasylan.com

