

DRIVOSOL[®] R290

Natural refrigerant

CAS NO.

Propane

74-98-6

APPLICATIONS & PROPERTIES

DRIVOSOL[®] R290 is a colorless, liquefied gas made from highly purified Propane.

PRODUCT SPECIFIC FEATURE

DRIVOSOL[®] R290 is an environmental friendly hydrocarbon and thus belongs to the group of natural refrigerants. Propane has a high energy efficiency with very good thermodynamic properties. Propane meets all requirements of the refrigeration technology.

APPLICATION FIELDS

Evonik's natural refrigerants R290, R600 & R600a can be used in almost any refrigeration application, such as refrigeration & freezing systems in private and commercial use, heat pumps, bottle coolers, air conditioners or refrigerated counters.

TRANSPORT & LOGISTICS

The delivery takes place in inspected and monitored means of transport in order to ensure the high quality standard of our DRIVOSOL[®] refrigerant, e.g. tank trucks, tank containers or rail tank cars.

Please contact us directly for individual mixtures of the natural refrigerants:

DRIVOSOL@evonik.com

SPECIFICATION

Property	Value	Unit	Method
Ethane (R170)	max. 0.2	% (w/w)	AA-0785-04-010*
Propane (R290)	min. 99.5	% (w/w)	AA-0785-04-010*
Isobutane (R600a)	max. 0.35	% (w/w)	AA-0785-04-010*
n-Butane (R600)	max. 0.15	% (w/w)	AA-0785-04-010*
1,3-Butadiene	max. 1	ppm (w/w)	AA-0785-04-011*
Sulphur	max. 0.5	ppm (w/w)	AA-0785-04-034*
Water	max. 10	ppm (w/w)	AA-0785-04-033*
Evaporation residue	max. 100	ppm (w/w)	AA-0785-04-123*

* in-house method

PHYSICAL PROPERTIES

Property	Value	Unit	Method
Odor	No foreign odors		AA-0785-04-121*
Pressure	7.8 ± 0.1	bar	AA-0785-04-126*
Density 20°C	0.500 ± 0.003	g/ml	DIN 51618
Color, appearance	clear		

* Inhouse method

CERTIFICATES

Current certifications according to DIN ISO 9001 and 14001 can be consulted on our website: www.evonik.com/C4-chemicals

DRIVOSOL® = is a registered trademark of Evonik Industries AG or its subsidiaries

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Oxeno GmbH & Co. KG

Paul-Baumann-Straße 1

45772 Marl

C4-chemicals@evonik.com

www.evonik.com/c4-chemicals

