

Dynasytan® OCTEO

Octyltriethoxysilane

Technical data

Properties and test methods	Value	Unit	Method
Boiling point (1013 hPa)	265/ 509	°C/ °F	DIN 51751
Density (20 °C / 68 ° F)	0.88	g/cm ³	DIN 51757
Viscosity (20 °C / 68 ° F)	2/ 2	mPa·s / cSt	DIN 53015
Flash point	> 93/ 199	°C/°F	DIN EN ISO 2719

Registrations

Dynasytan® OCTEO

EINECS/ELINCS (EU):	Yes
AICS (Australia):	Yes
DSL/NDSL (Canada):	Yes
PICCS (Philippines):	Yes
TSCA (USA):	Yes
IECSC (P.R. China):	Yes
ENCS (Japan):	Yes
ECL (South Korea):	Yes
NZIoC (New Zealand)	Yes
REACH (Europe)	Registered

Dynasytan® OCTEO is a monomeric medium-chain alkylfunctional silane.

Dynasytan® OCTEO is a clear colourless liquid and soluble in common non-polar organic solvents (e.g. petroleum ether, toluene). However its low volatility and viscosity make Dynasytan® OCTEO an easy-to-handle additive. During the hydrolysis reaction between water and Dynasytan® OCTEO a certain amount of ethanol (VOC) is released.

Safety and handling

Before considering the use of Dynasytan® products please read its Safety Data Sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available after registration on our website www.dynasytan.com or upon request from your local representative, customer service or from Evonik Operations GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

Packaging, storage and shelf life

Dynasytan® OCTEO is supplied in 25 kg pails, 175 kg drums and 870 kg IBC's.

In the unopened container Dynasytan® OCTEO silane has a shelf life of min. 12 months from delivery.

Properties and applications

Dynasylan® OCTEO silane can be used as a surface modifier to generate hydrophobicity on inorganic fillers and pigments, e.g. titandioxide. The medium-chain alkyl functionality results in unique compound properties when Dynasylan® OCTEO treated minerals or pigments are incorporated into polymers, e.g. polyethylene or polypropylene. Loading levels of 0.5 to 1.5wt.% Dynasylan® OCTEO based on the weight of filler or pigment are typically recommended.

Reactivity

Key Benefits:

Because of its unique structure, Dynasylan® OCTEO exhibits superior hydrophobicity on substrates and forms weather- and moisture-resistant bonds to substrates as well.

Use of Dynasylan® OCTEO silane results in:

- compatibility improvements between pigments or inorganic fillers and organic polymers or solvents, allowing easy pigment (e.g. iron oxides or titanium dioxide) or mineral filler (e.g. ATH, MDH) dispersion

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Europe/Middle-East/Africa

Evonik Operations GmbH

Silanes Business Line
Rodenbacher Chaussee 4
63457 Hanau-Wolfgang
Germany
FAX +49 6181 59 713915
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik (SEA) Pte. Ltd.

Silanes Business Line
3 Internatioanl Business Park
#07-18, Nordic European
Centre
Singapore 609927
PHONE +65 6809 6906
FAX +65 6809 6699
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Japan Co. Ltd

Silanes Business Line
12th Floor Monolith Building
2-3-1, Nishi-Shinjuku-ku
Tokyo 163-0912
Japan
PHONE +81 353 23 7446
FAX +81 353 23 7397
dynasytan@evonik.com
www.dynasytan.com

North America

Evonik Corporation

Silanes Business Line
299 Jefferson Road
Parsippany, NJ 07054
USA
PHONE (TOLL FREE) +1 800 237 67
45
PHONE +1 973 929 8513
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

**Evonik Specialty
Chemicals (Shanghai) Co. Ltd.**

Silanes Business Line
55, Chungdong Road
Xinzhuang Industry Park
Shanghai 201108
P.R. China
PHONE +86 21 61191-399
FAX +86 21 61191-648
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik India Pvt. Ltd.

Silanes Business Line
Krislon House
Saki Vihar Road, Anderi (E)
Mumbai - 400 072
India
PHONE +91 226 7238 809
FAX +91 226 7238 811
dynasytan@evonik.com
www.dynasytan.com

North America

Silbond Corporation

9901 Sand Creek Highway
Weston, MI 49289
USA
PHONE +1 732 981 5004
FAX +1 732 981 5275
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Korea Ltd.

Silanes Business Line
3F (Nongshim Sungmookwan
B/D)
112 Yeouidaebang-Ro
Dongjak-Gu
Seoul, 07057
Korea
PHONE +82 2320 4773
FAX +82 2783 2520
dynasytan@evonik.com
www.dynasytan.com

Region Central and South America

Evonik Brasil Ltda.

Silanes Business Line
Rua Arquiteto Olavo Redig de Campos,
105
Torre A - 04711-904 São Paulo- SP
Brazil
PHONE +55 11 3146 9627
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Taiwan Ltd.

Silanes Business Line
Artist Construction Bldg.
9F, No. 133
Min Sheng East Road, Sec 3
Taipei, 105 Taiwan, R.O.C.
Taiwan 10596
PHONE +886 227 17 1242 #247
FAX +886 227 17 2106
dynasytan@evonik.com
www.dynasytan.com