

Product Information

DYNOCEL® HG-LD

Dynocel HG-LD is a metal oxide promoted activated alumina for the removal of mercury to <10 ng/Sm³ from vapor and liquid phase hydrocarbon streams.

PRODUCT DESCRIPTION

Dynocel HG-LD is a lower density, co-formed metal oxide promoted activated alumina for the removal of mercury from vapor or liquid phase hydrocarbon streams. The metal oxide promoter is distributed homogenously throughout the adsorbent sphere providing uniform and predictable utilization of the Dynocel HG-LD.

Dynocel HG-LD offers high attrition resistance, high mechanical strength and high mercury adsorption capacity.

Typical Properties

Property	Unit	Value
Abrasion Loss	wt%	2.0
Bulk Density	- 40 lb / ft ³	36
Particle Size	in	1/8-1/16
Product Form		Spherical

The data represents typical values (no product specification)

TYPICAL APPLICATIONS

Mercury removal to <10 nanograms/Sm³ from vapor or liquid phase hydrocarbon streams such as LNG or natural gas.

BENEFITS & ADVANTAGES

+ Dynocel HG-LD is a low density, metal oxide promoted activated alumina for the removal of mercury to <10 nano-grams per Sm³ from vapor or liquid phase hydrocarbon streams.

+ Dynocel HG-LD has high mechanical strength which prevents alumina attrition over its life.

+ Dynocel HG-LD has a lower LCA vs activated carbon

HANDLING & PROCESSING

Dynocel HG-LD may be handled in air.

PACKAGING

1,576.2 (715 kg) supersacks

297.6 lbs (135 kg) steel drums

STORAGE

The material should be stored in its original container and in a dry, covered location protected from the ambient environment.

SHELF LIFE

5 years in original packaging stored in a dry, covered location

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH

Catalysts
Rodenbacher Chaussee 4
63457 Hanau
Germany
Phone +49 6181 59-13399
Fax +49 6181 59-2699
catalysts@evonik.com
evonik.click/catalysts