

Product Information

Dynasylan® 9896

Oligomeric alkylsilane condensate

PRODUCT DESCRIPTION

Dynasylan® 9896 is an oligomeric short-chain alkylfunctional silane.

Dynasylan® 9896 is a clear, colourless to slightly yellow liquid and soluble in common organic solvents (e.g. petroleum ether, toluene, alcohol). Because of its low volatility and viscosity Dynasylan® 9896 is an easy-to-handle additive.

During the hydrolysis reaction between water and Dynasylan® 9896 a certain amount of VOC (volatile organic compound) is released as ethanol. From an environmental standpoint it should be noted that the amount of released hydrolysis ethanol (VOC) is significantly reduced compared to monomeric alkyl silanes and is below 100 g/l.

The high boiling point of Dynasylan® 9896, together with its high flash point, gives outstanding advantages with respect to safety and handling during processing.

Typical Properties

Property	Unit	Value
Chemical Name		Oligomeric alkylalkoxysiloxane
Density DIN 51757 (@20 °C)	g/cm ³	1.04
Flash Point DIN EN ISO 2719	°C	≤63
pH Value 500 g/l water, 20 °C		3-4
Viscosity (20 °C) DIN 53015	mPa·s	60-60

The data represents typical values (no product specification)

TYPICAL APPLICATIONS

Dynasylan® 9896 silane can be used as a surface modifier to generate hydrophobicity (e.g. on inorganic pigments, mineral fillers). The short-chain alkyl functionality results in unique compound properties when Dynasylan® 9896

treated minerals or pigments are incorporated into polymers, e.g. polyethylene or polypropylene. Loading levels of 0.5 to 1.5 weight-% Dynasylan® 9896 based on the weight of filler or pigment are typically recommended. Dynasylan® 9896 is excellent as a dispersion and hydrophobation agent in mineral filled compounds. Dynasylan® 9896 forms covalent bonds to the inorganic and will not deplete in the final compound as it will happen to silicone oils used as surface modifiers. So Dynasylan® 9896 enables the printability of mineral filled plastics. In the presence of moisture, a low pH is created, the ethoxy groups of Dynasylan® 9896 hydrolyse to produce ethanol and reactive silanol groups. These silanol groups react with the filler via silicon-oxygen bridges. Dynasylan® 9896 can be used in many other applications such as filler and pigment coatings, dispersions etc. Typical property improvements obtained by using Dynasylan® 9896 in filled polymers are:

- improved filler dispersion
- good processability
- significantly reduced water-uptake

BENEFITS & ADVANTAGES

Because of its unique structure, Dynasylan® 9896 exhibits superior hydrophobicity on substrates and forms chemical bonds to substrates. Use of Dynasylan® 9896 silane results in:

- Particularly in non-polar media (e.g. polyolefins etc.). Dynasylan® 9896 treated inorganic substrates (e.g. titanium dioxide, ATH, or MDH) dispersion show excellent compatibility.
- Dynasylan® 9896 as all silanes forms covalent bonds and will not deplete in the final compound.
- Higher filler loadings are possible. Better compatibility results in lower viscosity compared to unmodified compounds.

HANDLING & PROCESSING

Before considering the use of Dynasylan® products please read its Safety Data Sheet (SDS) thoroughly for safety and

toxicological data as well as for information on proper transportation, storage and use.

The Safety Data Sheet is available upon request from your local representative, customer service or from Evonik Operations GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

PACKAGING

Dynasylan® 9896 950 kg non-returnable IBC totes (net weight).

Pails (25 kg) and polyethylene inlined steel drums (200 kg) are available as MTO.

STORAGE

The containers must remain tightly sealed and stored in a cool, well-ventilated place protected against moisture.

SHELF LIFE

In the unopened container Dynasylan® 9896 has a shelf life of min. 12 months from delivery.

Registration Listings

Registry	Status
Japan (ENCS)	Yes
South Korea (KECL)	Yes
Philippines (PICCS)	Yes
USA (TSCA)	Yes

Registration Listings

Registry	Status
Australia (AIIC)	No
Canada (DSL)	Information on Request
China (IECSC)	Information on Request
EU (EINECS/ELINCS)	Yes
EU (REACH)	Exempted

Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH

Smart Effects
Rodenbacher Chaussee 4
63457 Hanau
Germany
ask-se@evonik.com
ask-se-asia@evonik.com
ask-se-america@evonik.com
www.evonik.com/smarteffects