

**Product Information** 

# Dynasylan<sup>®</sup> SILBOND<sup>®</sup> H-5

#### Ethyl polysilicates binder

## **CAS NUMBER**

confidential

## **PRODUCT DESCRIPTION**

Dynasylan<sup>®</sup> SILBOND<sup>®</sup> H-5 is a clear, low-viscosity pre-hydrolyzed ethyl polysilicate binder that has been designed for the precision investment casting industry. It contains a higher percentage (approximately 19.5%) silica content (as  $SiO_2$ ) and a lower acidity level than Dynasylan<sup>®</sup> SILBOND<sup>®</sup> H-4.

Property	Unit	Value
Appearance		Clear Liquid
Boiling Point, min.	°C	78
Density	g/cm³	~0.92-0.93
(20 ° C)		
Flash Point, min.	°C	13
/iscosity	mPa·s	5.0
(20 ° C)		

The data represents typical values (no product specification)

# **TYPICAL APPLICATIONS**

It is well suited for use in block-casting applications.

Product Composition		
Product Composition	Unit	Value
Silicon Dioxide (SiO₂) Content	wt%	19.5-22.0

#### **BENEFITS & ADVANTAGES**

Dynasylan<sup>®</sup> SILBOND<sup>®</sup> H-5 can be used, as delivered, to make ceramic molds for the **Precision Investment Casting industry**.

The degree of hydrolysis and acidity have been optimized for the required reactivity and sufficient storage stability.

The hydrolysis and condensation has been started during the production of the binder. Through a shift in the pH this process is accelerated. This shift is achieved by addition of fillers, pigments, additive, or through the evaporation of solvent or exposure to atmospheric moisture. The resulting silicic acid gel cures rapidly at ambient temperatures in air. The process of curing can be accelerated through the addition of alkali catalysts.

## HANDLING & PROCESSING

Before considering the use of Dynasylan<sup>®</sup> SILBOND products please read its Safety Data Sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use.

The Safety Data Sheet is available on our website https:// silanes.evonik.com/en or upon request from your local representative, customer service or from Evonik Operations GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

#### PACKAGING

Dynasylan<sup>®</sup> SILBOND<sup>®</sup> H-5 could be available in pails, drums, totes and tanker quantities.

Please ask for further details.

#### **SHELF LIFE**

In unopened container Dynasylan<sup>®</sup> SILBOND<sup>®</sup> H-5 has a shelf life of min. 6 months from date of manufacture.



Registration Listings			
Status			
Yes			
	Yes Yes Yes Yes Yes Yes		

Registration Listings	
Registry	Status
New Zealand (NZIoC)	Yes
Philippines (PICCS)	Yes
Taiwan (TCSI)	Yes
United States of America (TSCA)	Yes

#### Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

#### Evonik Operations GmbH

Smart Effects Rodenbacher Chaussee 4 63457 Hanau Germany ask-se@evonik.com ask-se-asia@evonik.com ask-se-americas@evonik.com www.evonik.com/smarteffects

