

DESCRIPTION

ADDID® 230 is a solvent-free anti-static additive used to increase the conductivity of coating formulations.

KEY BENEFITS

- increases electrical conductivity
- good suitability for clear coatings
- very good compatibility even at high dosages

SUITABILITY

waterborne	solventborne
●	●
2-pack epoxy	2-pack polyurethane
●	●

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Floor coatings
- Wood coatings

TECHNICAL DATA

active matter content	100 %
appearance	yellowish clear liquid
chemical description	formulation of solid salts and quaternary nitrogen compounds
delivery form	liquid

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 1.0 - 8.0 wt-%

PROCESSING INSTRUCTIONS

- Stir before use!
- Addition to the grind as supplied is recommended.
- Incorporation in 2-pack formulations based on epoxy recommended into the amine component.
- Incorporation in 2-pack formulations based on polyurethane recommended into the polyol component.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com