

# ADDID® 700

## DESCRIPTION

ADDID® 700 is a highly effective deaerator concentrate that provides excellent effectiveness against micro-foam in solventborne, radiation-curing and high solids coatings. Very suitable for pigmented formulations.

## KEY BENEFITS

- highly recommended for pigmented formulations
- highly effective
- Prevents pinholes and solvent popping in bake coatings

## GRAPHICAL BAR

### Compressed air spraying



### Dip coating, flow coating, curtain coating



### Flooring



### Flexo/gravure printing



### Airless spraying



### Brush application/roller application



## SUITABILITY

### waterborne



### solventborne



### radiation-curing



### 1-pack coatings



### 2-pack epoxy



### 100% system



### 2-pack polyurethane



● not suitable ● partly suitable ● suitable

## TYPICAL APPLICATIONS

- Wood coatings
- Floor coatings

## TECHNICAL DATA

active matter content	100 %
delivery form	liquid

## SOLUBILITY

Mineral Spirits	TPGDA
●	●
Water	Acetone
●	●
n-Butylacetate (nBA)	Xylene
●	●
Butyl glycol	Styrene
●	●

● not soluble ● partly soluble ● soluble

## RECOMMENDED ADDITION LEVEL

As supplied on total formula weight: 0.1 - 1.0 %

## PROCESSING INSTRUCTIONS

- Stir before use!
- Additive must be incorporated with sufficiently high shear.
- Particular suitable for addition to the grind.

## HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)