

**DESCRIPTION**

ADDID® 911 is an adhesion promoter for solventborne and waterborne primers and coating formulations. It is based on an epoxy-functional silane.

**KEY BENEFITS**

promotes adhesion on metal, glass, and ceramic surfaces

**SUITABILITY**

waterborne	solventborne
●	●
polyurethane	alkyd resins
●	●
epoxy resins	polyester resins
●	●

● not suitable ● partly suitable ● suitable

**TECHNICAL DATA**

<b>active matter content</b>	100 %
<b>appearance</b>	clear liquid
<b>chemical description</b>	epoxy-functional alkoxy silane

**SOLUBILITY**

Water	Acetone
●	●
Butylacetate	n-Butanol
●	●
Methylethylketone	Methoxypropylacetat
●	●

● not soluble ● partly soluble ● soluble

**TYPICAL APPLICATIONS**

- Architectural paints
- General industrial coatings

**RECOMMENDED ADDITION LEVEL**

As supplied calculated on total formulation: 0.1 - 1.0 %

**PROCESSING INSTRUCTIONS**

- The product should be used at slightly acidic pH-values.
- The product hydrolyzes slowly in aqueous systems.
- Addition of acidic catalysts will promote hydrolysis.
- Addition in 2-pack formulations preferably in epoxy or isocyanate component.

**HANDLING & STORAGE**

When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)