



**DESCRIPTION**

TEGO® Addbond LTW-B improves adhesion and flexibility of solventborne coatings on steel, galvanized steel, aluminum, and plastics.

**KEY BENEFITS**

- excellent improvement of adhesion to metals and plastics
- improves corrosion resistance
- improves intercoat adhesion

**AREA OF APPLICATION****Adhesion on metal****Adhesion on plastic****Hardness****Flexibility****Viscosity reduction / increase of solids content****Fixation of aluminum pigments****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing**

● not suitable ● partly suitable ● suitable

**TYPICAL APPLICATIONS**

- General industrial coatings
- Can coatings
- Coil coatings
- Transportation coatings

**TECHNICAL DATA**

<b>active matter content</b>	60 %
<b>appearance</b>	clear liquid
<b>chemical description</b>	solution of a modified polyester
<b>hydroxy value (calculated on non-volatile content)</b>	Approx. 30 mg KOH/g
<b>solvent</b>	n-butylacetate
<b>viscosity at 23°C (as supplied)</b>	Approx. 500 mPas

**SOLUBILITY**

<b>Water</b>	<b>Ethanol</b>
●	●
<b>TPGDA</b>	<b>Acetone</b>
●	●
<b>Butylacetate</b>	<b>Mineral Spirits</b>
●	●

● not soluble ● partly soluble ● suitable

**RECOMMENDED ADDITION LEVEL**

Solid calculated on main binder solid: 3.0 - 15.0 %

**PROCESSING INSTRUCTIONS**

Addition as supplied during the let-down is recommended.

**HANDLING & STORAGE**

When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)