

TEGO® Airex 920

DESCRIPTION

TEGO® Airex 920 is a silicone-free deaerator concentrate that provides outstanding compatibility. Fast and efficient foam breakdown.

KEY BENEFITS

- universal use in clear and pigmented, radiation-curing formulations
- recoatable and glueable (silicone-free)
- suitable for UV inkjet

APPLICATION RECOMMENDATION

Brush application/roller application



Airless spraying



Compressed air spraying



Flexo/gravure printing



Dip coating, flow coating, curtain coating



Flooring



SUITABILITY

waterborne



solventborne



2-pack 100%



radiation-curing



pigmented coatings



clear coatings



● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Printing Inks
- Overprint varnishes
- Screen Inks
- Nail varnishes

TECHNICAL DATA

active matter content	100 %
appearance	colored liquid
chemical description	organic polymer, silicone-free

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.3 - 1.0 %

PROCESSING INSTRUCTIONS

- Predilution in a suitable solvent simplifies dosage and incorporation.
- Addition may be either in the grind or during the let-down procedure.
- Suitable for addition in clear formulations.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 60 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com