

TEGO® Airex 990

DESCRIPTION

- TEGO® Airex 990 shows very strong defoaming against both micro- and macro-foam in solventborne and high solids coatings. Especially for spray-applied coatings.
- TEGO® Airex 990 is a highly compatible deaerator concentrate that shows very high effectiveness in solventborne and high solids coatings. Very suitable for clear coats.

KEY BENEFITS

- excellent for sensitive coatings
- universal use for all application methods
- solvent-free

APPLICATION RECOMMENDATION

Brush application/roller application



Airless spraying



Compressed air spraying



Flexo/gravure printing



Dip coating, flow coating, curtain coating



Flooring



SUITABILITY

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
pigmented coatings	clear coatings
●	●

TYPICAL APPLICATIONS

- Furniture coatings
- Transportation coatings
- Plastic coatings
- Floor coatings

TECHNICAL DATA

active matter content	100 %
appearance	colored liquid
chemical description	formulation based on deaerating organic polymers, with a tip of silicone

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.2 - 1.0 %

PROCESSING INSTRUCTIONS

Addition as supplied is recommended.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 60 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com