


DESCRIPTION

TEGO® Color Aid 7062 is a compatibilizer for solventborne base paints. It can be post added to low polar base paints and helps the color acceptance of universal colorants.

KEY BENEFITS

- compatibilizer for universal colorants in solventborne paints
- works well with Pliolite-based paints

EFFECT**Color acceptance with organic pigments****Color acceptance with inorganic pigments****Influence on coating properties****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing****direct grind****resin-containing pigment concentrates****resin-free pigment concentrates****universal pastes**

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Architectural paints
- Universal pigment concentrates

TECHNICAL DATA

active matter content	approx. 90 %
amine value (as supplied)	Approx. 140 mg KOH/g
appearance	yellowish to brownish liquid
chemical description	surfactant with groups of high pigment affinity
solvent	isopropanol

SOLUBILITY**Water****Ethanol****TPGDA****Butylacetate****Mineral Spirits**

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.3 - 3.0 %

PROCESSING INSTRUCTIONS

- Add to the base paint before tinting.
- In certain cases, TEGO® Color Aid 7062 can be used to repair the already tinted paint.

HANDLING & STORAGE

- When stored in original unopened packaging, the product has a shelf life of 24 months from the date of manufacture.
- At low temperatures, reversible turbidity can occur.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com