

TEGO® Dispers 686

DESCRIPTION

TEGO® Dispers 686 is a wetting and dispersing additive for solventborne re-dispersible matting agent pastes. Wets and stabilizes matting agents in solventborne medium. Even after drying of the paste, it can still be used to produce a matte coating. Helps to achieve a homogenous distribution of matting agent.

KEY BENEFITS

- dried matting pastes are redispersible
- high loadings of matting agent possible
- 100% active and liquid

EFFECT

Viscosity reduction with organic pigments/carbon blacks



Color intensity/gloss with organic pigments/carbon blacks



Viscosity reduction with inorganic pigments/fillers



Color intensity/gloss with inorganic pigments/fillers



SUITABILITY

waterborne



solventborne



2-pack 100%



radiation-curing



direct grind



resin-containing pigment concentrates



resin-free pigment concentrates



● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

Wood coatings

TECHNICAL DATA

active matter content	100 %
appearance	clear to slightly hazy liquid
chemical description	high molecular weight polymer
viscosity at 25 °C	Approx. 300 mPas

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Butylacetate
●	●
Mineral Spirits	
●	

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on matting agent: 10 - 20 %

PROCESSING INSTRUCTIONS

Add to the grind before dispersion.

HANDLING & STORAGE

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com