

# TEGO® Dispers 717 W

## DESCRIPTION

TEGO® Dispers 717 W is an anionic wetting and dispersing additive for waterborne formulations. It combines very good viscosity reduction when used with inorganic pigments and enhanced compatibility of tinted paints.

## KEY BENEFITS

- good color acceptance
- very effective viscosity reduction
- good long-term stability

## EFFECT

### Viscosity reduction with organic pigments/carbon blacks



### Color intensity/gloss with organic pigments/carbon blacks



### Viscosity reduction with inorganic pigments/fillers



### Color intensity/gloss with inorganic pigments/fillers



## SUITABILITY

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
direct grind	resin-containing pigment concentrates
●	●
resin-free pigment concentrates	
●	

● not suitable ● partly suitable ● suitable

## TYPICAL APPLICATIONS

- Architectural paints
- Wood coatings

## TECHNICAL DATA

active matter content	approx. 40 %
appearance	yellowish clear liquid
chemical description	solution of a sodium salt of an acrylic polymer
pH-value	approx. 6 - 8
solvent	water

## SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

## RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.2 - 1.5 %

## PROCESSING INSTRUCTIONS

Add to the grind before dispersion.

## HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)