Slip and flow additive

TEGO® Glide 100

DESCRIPTION

TEGO® Glide 100 is highly compatible and suitable for a multitude of applications. It provides outstanding flow and leveling properties and medium slip.

KEY BENEFITS

- outstanding leveling properties
- highly compatible with clear coats
- recoatable

EFFECT

Anti-crater effect

Flow promotion

Slip effect

Anti-blocking

Low foam

SUITABILITY

waterborne	solventborne
●	●
2-pack 100%	**radiation-curing**
◪	●
pigmented coatings	**clear coatings**
●	●

○ not suitable ◪ partly suitable ● suitable

TYPICAL APPLICATIONS

- Car repair coatings
- Plastic coatings
- General industrial coatings
- Wood coatings

TECHNICAL DATA

active matter content	100 %
appearance	clear liquid
chemical description	polyether siloxane copolymer

SOLUBILITY

Water	Ethanol
●	●
TPGDA	**Acetone**
●	●
Butylacetate	**Mineral Spirits**
●	○

○ not soluble ◪ partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.05 - 0.5 %

PROCESSING INSTRUCTIONS

- Addition to the coating as supplied or as a predilution is possible.
- Predilution in a suitable solvent simplifies dosage and incorporation.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 60 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com

EVONIK Leading Beyond Chemistry