

DESCRIPTION

TEGO® Humectant 7000 is a humectant for resin-free pigment concentrates. It prevents caking and shows low influence on coating properties.

KEY BENEFITS

- prevents caking of colorants efficiently
- low influence on coating properties

SUITABILITY

waterborne	solventborne
●	●
direct grind	resin-containing pigment concentrates
●	●
resin-free pigment concentrates	universal pastes
●	●

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

Pigment concentrates

TECHNICAL DATA

active matter content	100 wt-%
appearance	clear liquid
pH value, 5% in water	7
viscosity at 25 °C	Approx. 200 mPas

SOLUBILITY

Mineral Spirits	Water
●	●
Acetone	Butyl glycol
●	●

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 5 - 15 wt-%

PROCESSING INSTRUCTIONS

Add before grinding.

HANDLING & STORAGE

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com