

**DESCRIPTION**

TEGO® Humectant 7005 is a humectant for resin-free pigment concentrates. It does not contribute to VOCs and its influence on coating properties is very low.

**KEY BENEFITS**

- prevents caking of colorants efficiently
- low influence on coating properties
- does not contribute to VOCs

**SUITABILITY**

waterborne	solventborne
●	●
direct grind	resin-containing pigment concentrates
●	●
resin-free pigment concentrates	universal pastes
●	●

● not suitable ● partly suitable ● suitable

**TYPICAL APPLICATIONS**

Pigment concentrates

**TECHNICAL DATA**

active matter content	100 wt-%
appearance	clear liquid
pH value, 5% in water	7
viscosity at 25 °C	Approx. 300 mPas

**SOLUBILITY**

Mineral Spirits	Water
●	●
Acetone	Butyl glycol
●	●

● not soluble ● partly soluble ● suitable

**RECOMMENDED ADDITION LEVEL**

As supplied calculated on total formulation: 5 - 15 wt-%

**PROCESSING INSTRUCTIONS**

Add before grinding.

**HANDLING & STORAGE**

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | [www.coating-additives.com](http://www.coating-additives.com)