

DESCRIPTION

REWOPAL® M 365 is a non-ionic wetting and dispersing additive for waterborne formulations. Helps the wetting of organic pigment. Can be used as co-dispersant in base paints.

KEY BENEFITS

- good wetting of organic pigments
- cost efficient

EFFECT**Viscosity reduction with organic pigments/carbon blacks****Color intensity/gloss with organic pigments/carbon blacks****Viscosity reduction with inorganic pigments/fillers****Color intensity/gloss with inorganic pigments/fillers****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing****direct grind****resin-containing pigment concentrates****resin-free pigment concentrates**

● not suitable ● partly suitable ● suitable

TECHNICAL DATA

active matter content	100 %
appearance	yellowish, light cloudy liquid
chemical description	ricinoleic acid polyglycol ester
pH-value	approx. 8

SOLUBILITY**Water****Ethanol****TPGDA****Butylacetate****Mineral Spirits**

● not suitable ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on pigment: 5.0 - 10.0 %

PROCESSING INSTRUCTIONS

- Add to the grind before dispersion.
- Post addition to the coating is also possible.

HANDLING & STORAGE

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

TYPICAL APPLICATIONS

- Architectural paints
- Pigment concentrates

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com