


DESCRIPTION

REWOPAL® B 2003 is a wetting and dispersing additive for waterborne formulations. Especially recommended for the millbase of silicate paints.

KEY BENEFITS

especially for silicate paints

EFFECT**Viscosity reduction with organic pigments/carbon blacks****Color intensity/gloss with organic pigments/carbon blacks****Viscosity reduction with inorganic pigments/fillers****Color intensity/gloss with inorganic pigments/fillers****SUITABILITY**

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
direct grind	resin-containing pigment concentrates
●	●
resin-free pigment concentrates	
●	

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

Architectural paints

TECHNICAL DATA

active matter content	approx. 35 %
appearance	yellowish clear liquid
chemical description	tetrasodium-N-(1,2-dicarboxyethyl)-N-alkylsulfosuccinate
pH-value	approx. 8
solvent	water

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 5.0 - 15.0 %

PROCESSING INSTRUCTIONS

- Add to the grind before dispersion.
- Post addition to the coating is also possible.

HANDLING & STORAGE

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com