


DESCRIPTION

TEGO® Rad 2650 is a radically cross-linkable release additive, providing utmost slip, strong release, and efficient defoaming properties. Ideal for pigmented inks.

KEY BENEFITS

- very strong slip and release properties
- efficient defoamer
- especially for pigmented systems

EFFECT**Substrate wetting****Flow promotion****Slip effect****Release****Defoaming effect****Clarity in varnishes****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing****pigmented coatings****clear coatings**

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

Printing Inks

TECHNICAL DATA

active matter content	100 %
appearance	clear to slightly hazy liquid
chemical description	silicone acrylate, radically cross-linkable

SOLUBILITY

Water	TPGDA
●	●
Acetone	Butylacetate
●	●
● not soluble ● partly soluble ● soluble	

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 2.0 % UV printing inks and overprint varnishes

As supplied calculated on total formulation: 0.1 - 1.0 % silk screen inks
As supplied calculated on total formulation: 0.1 - 1.5 % offset (litho) inks

PROCESSING INSTRUCTIONS

- Addition to the coating as supplied or as a predilution is possible.
- Stir before use!
- Upon prolonged storage, slight settlement might be observed. This does not affect the performance properties of the product.

HANDLING & STORAGE

When stored in an original unopened packaging the product has a shelf life of 48 months from the date of manufacture. The product should be stored out of direct sunlight.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com