

DESCRIPTION

SURFYNOL® 355 is a substrate wetting agent with global food contact compliances. It is suitable for waterborne coatings and inks.

KEY BENEFITS

- dynamic wetting on difficult-to-wet substrates
- good foam control
- suitable for food contact compliant formulations

EFFECT**Substrate wetting****Anti-crater effect****Flow promotion****Defoaming****Reduction of static surface tension****Reduction of dynamic surface tension****SUITABILITY**

waterborne	solventborne
●	●
2-pack 100%	radiation-curing
●	●
pigmented coatings	clear coatings
●	●

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Overprint varnishes
- Printing Inks
- Can coatings
- Liquid Inks

TECHNICAL DATA

active matter content	75 %
appearance	clear to hazy, colorless to colored liquid
chemical description	acetylenic-free surfactant
delivery form	liquid
solvent	water

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

PROCESSING INSTRUCTIONS

- Addition to the coating as supplied or as a predilution is possible.
- Can be introduced in the grind and let-down stage.

HANDLING & STORAGE

- When stored in original unopened packaging, the product has a shelf life of 24 months from the date of manufacture.
- Keep containers tightly closed in a dry, cool, and well-ventilated place. Product is freeze-thaw stable; if it phase separates or freezes at colder temperatures, warm container to 40 °C and mix thoroughly before use. Please refer to the SDS for the most current information.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com