

TEGO® Twin 4000**DESCRIPTION**

As a siloxane-based gemini surfactant, TEGO® Twin 4000 combines substrate wetting with good defoaming. It is very effective and suitable for a broad range of coatings.

KEY BENEFITS

- outstanding effectiveness
- excellent crater prevention and elimination
- suitable for waterborne, solventborne, and UV coatings

EFFECT**Substrate wetting****Anti-crater effect****Flow promotion****Defoaming****Reduction of static surface tension****Reduction of dynamic surface tension****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing****pigmented coatings****clear coatings**

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Printing Inks
- Wood coatings
- General industrial coatings
- Architectural paints

TECHNICAL DATA

active matter content	100 %
appearance	colored slightly hazy liquid
chemical description	siloxane-based gemini surfactant

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
●	●
Butylacetate	Mineral Spirits
●	●

● not soluble ● partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.05 - 0.5 %

PROCESSING INSTRUCTIONS

- Addition to the coating as supplied or as a predilution is possible.
- Add TEGO® Twin 4000 before any defoamer, flow, and/or substrate wetting additive. Check foam, wetting, and compatibility. Only add further additives if necessary.

HANDLING & STORAGE

When stored in an original unopened packaging, the product has a shelf life of 60 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com