

Film enhancer

TEGO® Variplus CA N

DESCRIPTION

TEGO® Variplus CA N shows excellent viscosity reduction and helps accelerate drying speed. It provides very good adhesion on metal combined with high gloss and good weather resistance.

KEY BENEFITS

- excellent viscosity reduction
- very good adhesion to metals
- excellent gloss improvement

EFFECT

Hardness



Gloss



Viscosity reduction / increase of solids content



Pigment wetting and stabilization



Adhesion improvement (e.g. metal, plastics)



SUITABILITY

waterborne



solventborne



radiation-curing



pigmented coatings



clear coatings



● not suitable ◐ partly suitable ● suitable

TYPICAL APPLICATIONS

- Printing Inks
- Ballpoint pen inks
- General industrial coatings
- Wood coatings

TECHNICAL DATA

active matter content	100 %
appearance	solid, flakes
chemical description	ketone-aldehyde condensation resin
glass transition temperature	Approx. 70 °C
hydroxyl value (as supplied)	approx. 200 mg KOH/g
solvent	-

SOLUBILITY

Water	Ethanol
●	●
TPGDA	Acetone
◐	●
Butylacetate	Mineral Spirits
●	●

● not soluble ◐ partly soluble ● soluble

RECOMMENDED ADDITION LEVEL

As supplied on total formula weight: 5 - 20 %

PROCESSING INSTRUCTIONS

- Dissolve in corresponding solvent before use.
- Addition to the grind or during the let-down is possible.
- Solutions in non-polar solvents may be turbid due to the water content of max. 4%.

HANDLING & STORAGE

When stored in an original unopened packaging between -10 and +30 °C, the product has a shelf life of at least 36 months from the date of manufacture. The product must be stored under the exclusion of air, light and moisture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com