

DESCRIPTION

TEGO® Viscoplus 3000 is a pH-independent, associative thickener with Newtonian flow behavior.

KEY BENEFITS

- provides nearly Newtonian flow behavior
- applicable in a broad range of waterborne coatings
- APEO- and tin-free

EFFECT**Structure viscosity****Sagging prevention****Settling prevention****Drag resistance****Spattering prevention****SUITABILITY****waterborne****solventborne****2-pack 100%****radiation-curing****pigmented coatings****clear coatings**

● not suitable ● partly suitable ● suitable

TYPICAL APPLICATIONS

- Architectural paints
- Printing Inks
- Wood coatings
- General industrial coatings

TECHNICAL DATA

active matter content	approx. 25 %
appearance	clear to hazy liquid
chemical description	non-ionic polyurethane solution
solvent	water

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 0.1 - 1.0 %

PROCESSING INSTRUCTIONS

- Addition to the coating also possible after production.
- Addition to the coating as supplied or as a pre-dilution is possible.

HANDLING & STORAGE

When stored in an original unopened packaging between +4 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com