# **ZEOFREE® 600**

## **DESCRIPTION**

ZEOFREE® 600 is a specialized precipitated synthetic calcium silicate with exceptionally high absorptive capacity. ZEOFREE® 600 has highly porous particles, making it an ideal carrier to deliver liquid materials in powder form or to impart uniquely absorptive qualities to the paint film.

#### **KEY BENEFITS**

- scavenger for leachable solubles in the film
- carrier for timed release of liquid ingredients
- carrier to compatibilize liquid ingredients
- anti-caking and free flow agent for powders

| <b>Ø</b>   | • |
|------------|---|
| waterborne |   |

## **TYPICAL APPLICATIONS**

- Architectural deep tinted colors
- · Stain-absorbing, stain-concealing primers
- Breathable facade and concrete coatings
- Specialty applications

| delivery form                  | free-flowing powder |
|--------------------------------|---------------------|
| il absorption                  | > 450 ml/100g       |
| loss on drying                 | 10 %                |
| particle size, d <sub>50</sub> | 8 µm                |
| H value, 5% in water           | 10                  |
| pecific gravity                | 2.1                 |
| pecific surface area (BET)     | 250 m²/g            |

#### **RECOMMENDED ADDITION LEVEL**

As supplied calculated on total formulation: 1 - 5 wt-%

# PROCESSING INSTRUCTIONS

It is recommended that this product be added, as supplied, to the grind.

#### HANDLING & STORAGE

When stored in its original unopened packaging, the product has a shelf life of 36 months from the date of manufacture. Evonik precipitated silicate products are extremely chemically stable. However, precipitated silicates, including this product, can absorb moisture and/or volatile organic compounds from the surrounding atmosphere. Therefore, we recommend storage in original sealed packaging and in a dry, cool place and removed from volatile organic substances. Even if a product is stored under these conditions, over periods of time the material may still pick up enough moisture to exceed the moisture content that is specified "as packaged" or at the time of packaging.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com

