ZETASPERSE® 175

DESCRIPTION

ZETASPERSE® 175 is a non-ionic wetting and dispersing additive with focus on pigment wetting. It shows outstanding color strength development when used as a co-dispersant to an anionic polymer. It improves color acceptance when used in the direct grind of a base paint.

KEY BENEFITS

- co-dispersant to improve pigment wetting
- improves color acceptance
- effective at low dosages

Viscosity reduction with organic pigments/carbon blacks Color intensity/gloss with organic pigments/carbon blacks Viscosity reduction with inorganic pigments/fillers Color intensity/gloss with inorganic pigments/fillers

waterborne solventborne 2-pack 100% radiation-curing direct grind resin-containing pigment concentrates resin-free pigment concentrates not suitable partly suitable suitable

TYPICAL APPLICATIONS

- Architectural paints
- Printing Inks
- General industrial coatings
- Wood coatings

TECHNICAL DATA

active matter content	50 %
appearance	clear, pale yellow liquid
chemical description	alcohol ethoxylate
HLB	17
solvent	water

Nater	Ethanol
•	•
TPGDA	Acetone
•	•
Butylacetate	Mineral Spirits
	•

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 1.0 - 3.0 %

PROCESSING INSTRUCTIONS

Add before grinding.

HANDLING & STORAGE

- Keep away from direct sunlight. Keep containers tightly closed in a
 dry, cool, and well-ventilated place. Product is freeze-thaw stable;
 however, if it phase separates or freezes, heat to 40-60°C to
 thoroughly melt and mix well before use. Please refer to the SDS for
 the most current information.
- When stored in an original unopened packaging, the product has a shelf life of 36 months from the date of manufacture.

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Operations GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com

